



# Flux-Ex Post Power

Aqueous, alkaline broadband cleaner

## PRODUCT DESCRIPTION

Stannol cleaner Flux-Ex Post Power is an alkaline broadband cleaning detergent for the thorough removal of flux residues, oxides and solder pastes after the soldering process. The powerful cleaning detergent is particularly suitable for assemblies, hybrids, stencils, misprints, solder frames and carriers as well as machine parts and magazines.

Flux-Ex Post Power is a ready-mix for direct use in a cleaning process.

## PRODUCT PROPERTIES

The product offers the following advantages:

- suitable for use at low temperatures
- low conductivity
- regenerable
- single-phase
- suitable for use in ultrasonic systems

## APPLICATION AREAS

TECHNICAL DATA	
pH-value [20 °C]	11,2
conductance [20 °C]	< 100 µS/cm
flash-point	> 100 °C
VOC content	< 20 %
application	undiluted
water solubility	fully soluble
application temperature	20 - 45 °C

CONTAMINATIONS	
solder paste	++
flux	++
oxides	++
grease/oil	++
adhesive/glue	0
thermal compounds	-
solder wire	+

SUBSTRATES	
PCBAs, hybrids, power electronics, misprints (mounted)	++
stencils, screens, misprints (bare boards)	+
solder frames, carriers, solder masks	o
ESD boxes, containers, magazines	o
condensation traps, filters, steel sheets	o

APPLICATIONS	
spray systems	++
dipping	++
ultrasound systems	+
manual application	o

++ = ideal for use, + = recommended, o = optional use, - = not recommended

**Please note:** These tables only provide a general overview of the cleaner's specifications. To determine the ideal setting of the cleaner, cleaning tests are useful and necessary.

## STORAGE AND SHELF-LIFE

---

The shelf life is unlimited if stored and transported appropriately (protected from UV light, in the unopened original container, between 10 °C and 30 °C). After opening, the shelf life is at least two years if stored and transported correctly. It is recommended to use the cleaning detergent within five years of delivery.

## HEALTH AND SAFETY

---

Read the safety data sheet before first use and follow the safety precautions.

## DELIVERY FORMS

---

- 10 l canister
- 25 l canister

## DISCLAIMER

---

The above values are typical and represent no form of specification. The Data Sheet serves for information purposes. Any verbal or written advise is not binding for the company, whether such information originates from the company offices or from a sales representative. This is also in respect of any protection rights of third parties, and does not release the customer from the responsibility of verifying the products of the company for suitability of use for the intended process or purpose. Should any liability on the part of the company arise, the company will only indemnify for loss or damage to the same extent as for defects in quality.