



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 22.02.2023

Version number 3.3 (replaces version 3.2)

Revision: 22.02.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: **Flux HW 139**

1.2 Relevant identified uses of the substance or mixture and uses advised against

- Technical function soldering
- Application of the substance / the mixture Soldering flux

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:
Stannol GmbH & Co. KG
Haberstrasse 24
D-42551 Velbert

+49 (0) 2051 3120 332
sdb@stannol.de

Further information obtainable from: Product Safety Department

1.4 Emergency telephone number:
8:00 am - 5:00 pm (CET) +49 (0) 2051 3120 332

National Poisons Information Service
+44 121 507 4123

Members of the public seeking specific information on poisons should contact:
In England and Wales: NHS 111 - dial 111
In Scotland: NHS 24 - dial 111

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 3 H226 Flammable liquid and vapour.
Skin Irrit. 2 H315 Causes skin irritation.
Eye Irrit. 2 H319 Causes serious eye irritation.
Repr. 2 H361d Suspected of damaging the unborn child.
STOT SE 3 H336 May cause drowsiness or dizziness.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

Hazard pictograms



GHS02



GHS07



GHS08

Signal word Warning

Hazard-determining components of labelling:

propan-2-ol
2-methylpentane-2,4-diol

Hazard statements

H226 Flammable liquid and vapour.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H361d Suspected of damaging the unborn child.
H336 May cause drowsiness or dizziness.

Precautionary statements

P201 Obtain special instructions before use.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

(Contd. on page 2)
GB



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 22.02.2023

Version number 3.3 (replaces version 3.2)

Revision: 22.02.2023

Trade name: Flux HW 139

(Contd. of page 1)

- P271 Use only outdoors or in a well-ventilated area.
- P280 Wear protective gloves / eye protection.
- P280 Wear protective clothing.
- P302+P352 IF ON SKIN: Wash with plenty of soap and water.
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P308+P313 IF exposed or concerned: Get medical advice/attention.
- P332+P313 If skin irritation occurs: Get medical advice/attention.
- P337+P313 If eye irritation persists: Get medical advice/attention.
- P403+P235 Store in a well-ventilated place. Keep cool.
- P405 Store locked up.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

2.3 Other hazards

Flux / flux gels:

Inhalation of vapors released during the soldering process should be avoided. Flux vapors irritate the nose, throat, and respiratory tract, and can lead to allergic reactions (asthma) after prolonged or repeated contact. Therefore, an active suction is recommended.

After working with the product and before eating, drinking or smoking, wash your hands with soap and water.

Keep out of the reach of children.

Results of PBT and vPvB assessment

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients**3.2 Mixtures**

- **Description:** Mixture of substances listed below with nonhazardous additions.

Dangerous components:

CAS: 67-63-0	propan-2-ol	Flam. Liq. 2, H225	15 - 45%
EINECS: 200-661-7		Eye Irrit. 2, H319; STOT SE 3, H336	
CAS: 107-41-5	2-methylpentane-2,4-diol	Repr. 2, H361d	2 - 9%
EINECS: 203-489-0		Skin Irrit. 2, H315; Eye Irrit. 2, H319	
CAS: 110-94-1	glutaric acid	Skin Corr. 1A, H314; Eye Dam. 1, H318	≤ 2.5%
EINECS: 203-817-2			

- **Additional information:** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures**4.1 Description of first aid measures**

- **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.

- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures**5.1 Extinguishing media****Suitable extinguishing agents:**

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

For safety reasons unsuitable extinguishing agents: Water with full jet

- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.

(Contd. on page 3)
GB



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 22.02.2023

Version number 3.3 (replaces version 3.2)

Revision: 22.02.2023

Trade name: Flux HW 139

(Contd. of page 2)

- **5.3 Advice for firefighters**
- **Protective equipment:** No special measures required.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Ensure adequate ventilation
Wear protective clothing.
- **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Open and handle receptacle with care.
- **Information about fire - and explosion protection:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Keep respiratory protective device available.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep container tightly sealed.
- **Storage class:** 3
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **8.1 Control parameters**
- **Ingredients with limit values that require monitoring at the workplace:**
CAS: 67-63-0 propan-2-ol
WEL (Great Britain) Short-term value: 1250 mg/m³, 500 ppm
Long-term value: 999 mg/m³, 400 ppm
CAS: 107-41-5 2-methylpentane-2,4-diol
WEL (Great Britain) Short-term value: 123 mg/m³, 25 ppm
Long-term value: 123 mg/m³, 25 ppm
- **Additional information:** The lists valid during the making were used as basis.
- **8.2 Exposure controls**
- **Appropriate engineering controls** No further data; see item 7.
- **Individual protection measures, such as personal protective equipment**
- **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Store protective clothing separately.
Avoid contact with the eyes and skin.
- **Respiratory protection:**
Not necessary if room is well-ventilated.

(Contd. on page 4)
GB



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 22.02.2023

Version number 3.3 (replaces version 3.2)

Revision: 22.02.2023

Trade name: Flux HW 139

(Contd. of page 3)

Use suitable respiratory protective device in case of insufficient ventilation.

Filter A

· **Hand protection**



Protective gloves

Solvent resistant gloves

Rubber gloves

Synthetic rubber gloves

To avoid skin problems reduce the wearing of gloves to the required minimum.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

Nitrile rubber, NBR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The determined penetration times according to EN 16523-1:2015 are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye/face protection** Safety glasses

SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· **Physical state**

Fluid

· **Colour:**

Clear

· **Odour:**

Characteristic

· **Odour threshold:**

Not determined.

· **Melting point/freezing point:**

Undetermined.

· **Boiling point or initial boiling point and boiling range**

82 °C

· **Flammability**

Flammable.

· **Lower and upper explosion limit**

· **Lower:**

Not determined.

· **Upper:**

Not determined.

· **Flash point:**

26 °C

· **Decomposition temperature:**

Not determined.

· **pH**

Not determined.

· **Viscosity:**

· **Kinematic viscosity**

Not determined.

· **Dynamic:**

Not determined.

· **Solubility**

· **water:**

Not miscible or difficult to mix.

· **Partition coefficient n-octanol/water (log value)**

Not determined.

· **Vapour pressure:**

Not determined.

· **Density and/or relative density**

· **Density:**

Not determined.

· **Relative density**

Not determined.

· **Vapour density**

Not determined.

(Contd. on page 5)
GB



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 22.02.2023

Version number 3.3 (replaces version 3.2)

Revision: 22.02.2023

Trade name: Flux HW 139

(Contd. of page 4)

· 9.2 Other information

· Appearance:

· Form: Fluid

· Important information on protection of health and environment, and on safety.

· Auto-ignition temperature:

Product is not selfigniting.

· Explosive properties:

Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

· Solvent content:

· Organic solvents:

45.0 %

· Water:

47.4 %

· VOC (EC)

45.00 %

· Change in condition

· Evaporation rate

Not determined.

· Information with regard to physical hazard classes

· Explosives

Void

· Flammable gases

Void

· Aerosols

Void

· Oxidising gases

Void

· Gases under pressure

Void

· Flammable liquids

Flammable liquid and vapour.

· Flammable solids

Void

· Self-reactive substances and mixtures

Void

· Pyrophoric liquids

Void

· Pyrophoric solids

Void

· Self-heating substances and mixtures

Void

· Substances and mixtures, which emit flammable gases in contact with water

Void

· Oxidising liquids

Void

· Oxidising solids

Void

· Organic peroxides

Void

· Corrosive to metals

Void

· Desensitised explosives

Void

SECTION 10: Stability and reactivity

· **10.1 Reactivity** No further relevant information available.

· 10.2 Chemical stability

· **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.

· **10.3 Possibility of hazardous reactions** No dangerous reactions known.

· **10.4 Conditions to avoid** No further relevant information available.

· **10.5 Incompatible materials:** No further relevant information available.

· **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

· 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

· **Acute toxicity** Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

CAS: 67-63-0 propan-2-ol

Oral LD50 5,045 mg/kg (rat)

Dermal LD50 12,800 mg/kg (rabbit)

Inhalative LC50/4 h 30 mg/l (rat)

(Contd. on page 6)
GB



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 22.02.2023

Version number 3.3 (replaces version 3.2)

Revision: 22.02.2023

Trade name: Flux HW 139

(Contd. of page 5)

- **Skin corrosion/irritation** Causes skin irritation.
- **Serious eye damage/irritation** Causes serious eye irritation.
- **Reproductive toxicity** Suspected of damaging the unborn child.
- **STOT-single exposure** May cause drowsiness or dizziness.
- **11.2 Information on other hazards**
- **Endocrine disrupting properties**
None of the ingredients is listed.


SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Endocrine disrupting properties** The product does not contain substances with endocrine disrupting properties.
- **12.7 Other adverse effects**
- **Additional ecological information:**
- **General notes:**
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:** Packagings that may not be cleansed are to be disposed of in the same manner as the product.

SECTION 14: Transport information

- **14.1 UN number or ID number**
- **ADR, IMDG, IATA** UN1219
- **14.2 UN proper shipping name**
- **ADR** 1219 ISOPROPANOL (ISOPROPYL ALCOHOL) solution
- **IMDG, IATA** ISOPROPANOL (ISOPROPYL ALCOHOL) solution
- **14.3 Transport hazard class(es)**
- **ADR, IMDG, IATA**
- 
- **Class** 3 Flammable liquids.
- **Label** 3
- **14.4 Packing group**
- **ADR, IMDG, IATA** II

(Contd. on page 7)
GB



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 22.02.2023

Version number 3.3 (replaces version 3.2)

Revision: 22.02.2023

Trade name: Flux HW 139

(Contd. of page 6)

- **14.5 Environmental hazards:** Not applicable.
- **14.6 Special precautions for user** Warning: Flammable liquids.
- **Hazard identification number (Kemler code):** 30
- **EMS Number:** F-E,S-D
- **Stowage Category** B
- **14.7 Maritime transport in bulk according to IMO instruments** Not applicable.
- **Transport/Additional information:**
- **ADR**
- **Limited quantities (LQ)** 1L
- **Excepted quantities (EQ)** Code: E2
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 500 ml
- **Transport category** 2
- **Tunnel restriction code** D/E
- **IMDG**
- **Limited quantities (LQ)** 1L
- **Excepted quantities (EQ)** Code: E2
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 500 ml
- **UN "Model Regulation":** UN 1219 ISOPROPANOL (ISOPROPYL ALCOHOL) SOLUTION, 3, II

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the GB CLP regulation.
- **Hazard pictograms**



GHS02 GHS07 GHS08

- **Signal word** Warning
- **Hazard-determining components of labelling:**
propan-2-ol
2-methylpentane-2,4-diol
- **Hazard statements**
H226 Flammable liquid and vapour.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H361d Suspected of damaging the unborn child.
H336 May cause drowsiness or dizziness.
- **Precautionary statements**
P201 Obtain special instructions before use.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves / eye protection.
P280 Wear protective clothing.
P302+P352 IF ON SKIN: Wash with plenty of soap and water.

(Contd. on page 8)
GB



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 22.02.2023

Version number 3.3 (replaces version 3.2)

Revision: 22.02.2023

Trade name: Flux HW 139

(Contd. of page 7)

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P332+P313 If skin irritation occurs: Get medical advice/attention.

P337+P313 If eye irritation persists: Get medical advice/attention.

P403+P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category** P5c FLAMMABLE LIQUIDS
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 5,000 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 50,000 t
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**
 - H225 Highly flammable liquid and vapour.
 - H314 Causes severe skin burns and eye damage.
 - H315 Causes skin irritation.
 - H318 Causes serious eye damage.
 - H319 Causes serious eye irritation.
 - H336 May cause drowsiness or dizziness.
 - H361d Suspected of damaging the unborn child.
- **Department issuing SDS:** Product Safety Department
- **Contact:** Hr. Dörr
- **Abbreviations and acronyms:**
 - ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
 - IMDG: International Maritime Code for Dangerous Goods
 - IATA: International Air Transport Association
 - GHS: Globally Harmonised System of Classification and Labelling of Chemicals
 - EINECS: European Inventory of Existing Commercial Chemical Substances
 - ELINCS: European List of Notified Chemical Substances
 - CAS: Chemical Abstracts Service (division of the American Chemical Society)
 - VOC: Volatile Organic Compounds (USA, EU)
 - LC50: Lethal concentration, 50 percent
 - LD50: Lethal dose, 50 percent
 - PBT: Persistent, Bioaccumulative and Toxic
 - vPvB: very Persistent and very Bioaccumulative
 - Flam. Liq. 2: Flammable liquids – Category 2
 - Flam. Liq. 3: Flammable liquids – Category 3
 - Skin Corr. 1A: Skin corrosion/irritation – Category 1A
 - Skin Irrit. 2: Skin corrosion/irritation – Category 2
 - Eye Dam. 1: Serious eye damage/eye irritation – Category 1
 - Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
 - Repr. 2: Reproductive toxicity – Category 2
 - STOT SE 3: Specific target organ toxicity (single exposure) – Category 3